

LX80-1

1.5 Cubic Ft. Ultra-Low Freezer



-86°C Temperature Upright Freezer

Used by universities, hospitals and research institutes for long term storing of blood, skin cells, DNA, organs, and vaccines

Digital controller with potential free contact (which makes it possible to connect it to an external alarm)

Temperature Range (°C)

-40° to -86°

Exterior WxDxH (In)

25 x 20.6 x 31.5

Internal WxDxH (In)

17.1 x 12.4 x 11.4

Capacity(Cu.FT)

1.5

Weight (lbs)

142

Model

Cabinet Type	Upright
Capacity (Cu.Ft)	1.5
Internal Size (WxDxH) inches	17.1 x 12.4 x 11.4
External Size (WxDxH) inches	25 x 20.6 x 31.5
NW(Lbs)	142

Performance

Temperature Range (C°)	-54°~ -86°
Ambient Temperature	10°-30°
Controller	Microprocessor
Display	Digital display

Refrigeration

Compressor	Single Auto-Cascade
Cooling Method	Static
Defrost Mode	Manual
Refrigerant	Mixed HC
Insulation (mm)	100

Construction

Inner Material	304 Stainless Steel
Inner Doors	1 Stainless Steel
Shelves	1 Stainless Steel
Door Lock with Key	Yes
Port	1pc. Ø 12mm
Casters	4

Alarm

Temperature	High/Low temperature,
-------------	-----------------------

Electrical

Power Supply(V/HZ)	115/60
Power Consumption (KW/Hr)	3.8/24

Due to periodic changes in designs, methods, procedures, policies and regulations, the specifications contained in this sheet are subject to change without notice. While we exercise good faith efforts to provide information that is accurate, we are not responsible for errors or omissions in information provided or conclusions reached as a result of using the specifications. By using the information provided, the user assumes all risks in connection with such use.



This unit comes with a standard 1 year warranty.